

### DH151

#### **General Features**

The model DH151 grinder pump station is a complete unit that includes: the grinder pump, check valve, polyethylene tank, controls, and alarm panel. A single DH151 is a popular choice for up to two, average single-family homes and can also be used for up to six average single-family homes where codes allow and with consent of the factory.

- Rated for flows of 1500 gpd (5678 lpd)
- · 150 gallons (568 liters) of capacity
- · Indoor or outdoor installation
- · Standard outdoor heights range from 63 inches to 160 inches

The DH151 has a cable that connects the motor controls to the level controls through watertight penetrations.

#### **Operational Information**

#### Motor

1 hp, 1,725 rpm, high torque, capacitor start, thermally protected, 120/240V, 60 Hz, 1 phase

#### Inlet Connections

4-inch inlet grommet standard for DWV pipe. Other inlet configurations available from the factory.

#### Discharge Connections

Pump discharge terminates in 1.25-inch NPT female thread. Can easily be adapted to 1.25-inch PVC pipe or any other material required by local codes.

#### Discharge

15 gpm at 0 psig (0.95 lps at 0 m)

11 gpm at 40 psig (0.69 lps at 28 m)


7.8 gpm at 80 psig (0.49 lps at 56 m)


#### Accessories

E/One requires that the Uni-Lateral, E/One's own stainless steel check valve, be installed between the grinder pump station and the street main for added protection against backflow.


Alarm panels are available with a variety of options, from basic monitoring to advanced notice of service requirements.

The Remote Sentry is ideal for installations where the alarm panel may be hidden from view.





## DH151-47 INDOOR UNIT



NOTE: DIMENSIONS ARE FOR REFERENCE ONLY










| LNT   | GAE   | 04/24/07 | В     |       |
|-------|-------|----------|-------|-------|
| DR BY | CHK'D | DATE     | ISSUE | SCALE |
|       |       |          |       |       |



MODEL DH151-47





NOTE: DIMENSIONS ARE FOR REFERENCE ONLY

DISCHARGE: 1-1/4 in FEMALE PIPE THREAD

INLET: EPDM GROMMET FOR 4" DWV PIPE (STANDARD)










| JVL   | JG    | 6/24/2024 | D     | 1:12  |
|-------|-------|-----------|-------|-------|
| DR BY | CHK'D | DATE      | ISSUE | SCALE |



**MODEL DH151-63** 



SEE INSTALLATION INSTRUCTIONS FOR DETAILS

NOTE: DIMENSIONS ARE FOR REFERENCE ONLY

DISCHARGE: 1-1/4 in FEMALE PIPE THREAD


INLET: EPDM GROMMET FOR 4" DWV PIPE (STANDARD)



**MODEL DH151-74** 

NA0051P06

### DH151-93





NOTE: DIMENSIONS ARE FOR REFERENCE ONLY

DISCHARGE: 1-1/4 in FEMALE PIPE THREAD

INLET: EPDM GROMMET FOR 4" DWV PIPE (STANDARD)








| JVL   | JG    | 6/24/2024 | E     | 1:16  |
|-------|-------|-----------|-------|-------|
| DR BY | CHK'D | DATE      | ISSUE | SCALE |
|       |       |           |       |       |




**MODEL DH151-93** 



# DH151-59 BUILDERS MODEL

STRAIGHT DISCHARGE











AD CAH 06/27/07 C 1/16

DR BY CHK'D DATE ISSUE SCALE




MODEL DH151-59 BUILDERS

NA0051P09

NOTE: DIMENSIONS ARE FOR REFERENCE ONLY

## DH151-59 BUILDERS MODEL

OUTSIDE TYPE DISCHARGE











| AD    | CAH     | 06/27/07 | С     | 1/16  |
|-------|---------|----------|-------|-------|
| DR BY | CHK ' D | DATE     | ISSUE | SCALE |
|       |         |          |       |       |



MODEL DH151-59 BUILDERS

NA0051P10

NOTE: DIMENSIONS ARE FOR REFERENCE ONLY